

- GENERAL ELEVATION NOTES:**
- 1.0 ALL WINDOW HDR. HTS. LOWER FLOOR TO BE 8'-0" A.F.F. UNLESS NOTED OTHERWISE ON FLOOR PLANS. ALL WINDOW HDR. HTS. UPPER FLOOR TO BE 6'-8" A.F.F. UNLESS NOTED OTHERWISE ON FLOOR PLANS.
  - 2.0 MAXIMUM 18" EXPOSED FOUNDATION ABOVE FINISHED GRADE OR PER SUBDIVISION REQUIREMENTS.
  - 3.0 GRADE LINES SHOWN ON ELEVATION DRAWINGS SHALL NOT BE CONSTRUED TO REPRESENT ACTUAL FINISH GRADES. VERIFY FINISH GRADE ON JOB SITE.
  - 4.0 ACTUAL ELEVATIONS TO VARY PER GRADE OF EXISTING LOT.
  - 5.0 ALL PLUMBING, APPLIANCE AND GAS VENTS TO BE GANGED TO THE FEWEST NUMBER POSSIBLE PENETRATING THE ROOF AND KEPT TO REAR OF ROOF WHEREVER POSSIBLE.
  - 6.0 CHIMNEY/FLUE SHOWN AT MINIMUM DIMENSIONAL HEIGHT REQUIREMENTS PER CODE. BUILDER RESPONSIBLE FOR CONSTRUCTING CHIMNEY/FLUE TO ENSURE PROPER DRAW FOR FIREPLACE BASED ON HOUSE & SITE ORIENTATION VERSUS PREVAILING WINDS.

**GENERAL PROJECT NOTES:**

- 1.0 THESE CONSTRUCTION DOCUMENTS ARE INTENDED TO MEET ALL APPLICABLE CODES AND ORDINANCES. CONTRACTOR TO COMPLY WITH ALL LOCAL CODES, ORDINANCES AND DEED RESTRICTIONS. CONTRACTOR SHALL ALSO REQUIRE ALL SUBCONTRACTORS TO COMPLY WITH THESE REGULATIONS.
- 2.0 ANY DISCREPANCIES IN CONSTRUCTION DOCUMENTS OR NONCOMPLIANCE TO BE BROUGHT TO THE ATTENTION OF THE DESIGNER PRIOR TO ANY WORK BEING PERFORMED OR MATERIALS BEING ORDERED. BUILDER ACCEPTS FULL RESPONSIBILITY FOR CHECKING PLANS TO ASSURE CONFORMITY TO CURRENT LOCAL BUILDING CODES. SHOULD ANY CHANGES BE MADE TO THESE PLANS BY BUILDER OR HIS REPRESENTATIVES WITHOUT CONTACTING THE DESIGNER, THE BUILDER WILL ACCEPT FULL LIABILITY FOR AMENDED PLANS.
- 3.0 WHILE THESE DRAWINGS ARE INTENDED TO SHOW SAME, THE DESIGNER IS NOT RESPONSIBLE FOR GOVERNING AUTHORITY INTERPRETATIONS WHERE THOSE INTERPRETATIONS CONFLICT WITH THESE DRAWINGS &/OR SPECS.
- 4.0 THESE DRAWINGS HAVE NOT BEEN DRAWN BY A REGISTERED ARCHITECT.
- 5.0 THESE DRAWINGS/SPECS ARE INSTRUMENTS OF SERVICE AND SHALL REMAIN THE PROPERTY OF THE DESIGNER WHETHER THE PROJECT IS EXECUTED OR NOT. THESE DRAWINGS SHALL NOT BE USED BY THE CLIENT FOR OTHER PROJECTS, FOR ADDITIONS TO THIS PROJECT, OR FOR COMPLETION OF THIS PROJECT BY OTHERS WITHOUT PERMISSION OF THE DESIGNER.
- 6.0 THESE DOCUMENTS DO NOT SHOW TYPICAL DETAILING &/OR WATERPROOFING.
- 7.0 THESE DOCUMENTS DO NOT SPECIFY ACTUAL PRODUCTS OR MATERIAL SELECTIONS. CONTRACTOR ACCEPTS FULL RESPONSIBILITY FOR APPROPRIATE AND PROPER DETAILING FOR AND BETWEEN ALL ACTUAL PRODUCTS/MATERIALS SELECTED WHEN INSTALLED.
- 8.0 ALL COMPONENTS, MATERIALS, ASSEMBLIES AND FINISHES TO BE CONSTRUCTED AND INSTALLED PER MANUFACTURER'S RECOMMENDATIONS, CODE REQUIREMENTS AND REGULATED BUILDING PRACTICES.
- 9.0 DESIGNER IS NOT RESPONSIBLE FOR MEANS AND METHODS OF CONSTRUCTION WHICH ARE NOT DETAILED IN THESE CONSTRUCTION DOCUMENTS. CONTRACTOR WILL BE RESPONSIBLE FOR ALL ASPECTS OF CONSTRUCTION INCLUDING BUT NOT LIMITED TO ALL WATER AND DAMP PROOFING, LOAD CONNECTIONS AND MECHANIC, ELECTRICAL AND PLUMBING SYSTEMS.

**GENERAL PLAN NOTES:**

- 1.0 ALL WINDOWS WILL BE DIMENSIONED TO CENTER LINE UNLESS OTHERWISE NOTED. GLASS SIZE PER MFR. SPECS.
- 2.0 ALL WINDOWS WITHIN 24" OF AN EXTERIOR OR INTERIOR DOOR TO BE TEMPERED GLASS. WINDOW MANUFACTURER TO VERIFY FOR ALL TEMPERED GLASS LOCATIONS AS PER APPLICABLE CODE.
- 3.0 ALL HINGED SHOWER DOORS SHALL SWING OUTWARD. GLAZING USED IN DOORS AND PANELS OF BATHTUB/SHOWER ENCLOSURES AND BUILDING WALLS ENCLOSING THESE COMPARTMENTS SHALL BE FULLY TEMPERED OR LAMINATED SAFETY GLASS.
- 4.0 WINDOW MANUFACTURER & BUILDER TO VERIFY EGRESSABLE WINDOWS INSTALLED WHERE REQUIRED BY CODE.
- 5.0 PROVIDE BLOCKING FOR CEILING FANS WHERE SPECIFIED.
- 6.0 PROVIDE ELECTRIC FOR POOL &/OR SPA EQUIP. & LIGHTS. PROVIDE NECESSARY PLUMBING FOR POOL &/OR SPA. VERIFY LOCATION WITH BUILDER OR OWNER.
- 7.0 BUILDER TO VERIFY SIZING AND LOCATION OF ALL APPLIANCES & RELATED COMPONENTS.
- 8.0 WEATHERSTRIP ATTIC ACCESS DOOR(S).
- 9.0 CONTRACTOR TO PROVIDE A 3/4" PLYWOOD CATWALK FROM ATTIC ACCESS TO HVAC UNITS (IF APPLICABLE). UNITS TO BE LOCATED WITHIN 20'-0" OF ACCESS.
- 10.0 PROVIDE 1 S.F. NET FREE AREA OF ATTIC VENTILLATION PER 150 S.F. OF TOTAL COVERED ROOF AREA AS PER CODE.
- 11.0 IF PLATE HEIGHT IS 10'-0" OR HIGHER, ALL DOORS AND CASED OPENINGS TO BE 8'-0" HT. UNLESS NOTED OTHERWISE. IF PLATE HEIGHT IS 9'-0" OR LESS, ALL DOORS AND CASED OPENINGS TO BE 6'-8" HT. UNLESS NOTED OTHERWISE. EXCEPTION, IF A 7'-0" HT. DOOR IS USED ADJUST WINDOWS TO 7'-0" HEADER HT.

**LEGEND:**


⚡ GAS    ⚡ GAS KEY    🚿 SHOWER HEAD    🚿 HOSE BIBB

**GENERAL ROOF LAYOUT NOTES:**

- 1.0 PITCHES TO BE AS NOTED ON PLANS.
- 2.0 HIPS, VALLEYS & RIDGES TO BE FRAMED ONE SIZE LARGER THAN RAFTERS.
- 3.0 ALL PLUMBING, APPLIANCE AND GAS VENTS TO VENT TO REAR OF ROOF RIDGE WHEREVER POSSIBLE. ALL VENTS TO BE GANGED TO THE FEWEST NUMBER POSSIBLE PENETRATING THE ROOF.
- 4.0 ALL OVERHANGS TO BE 24" FROM THE FRAMEWALL UNLESS NOTED OTHERWISE.
- 5.0 U.N.O. ALL INTERIOR WALLS OF ONE STORY PLANS TO BE LOAD BEARING.
- 6.0 HATCHED AREAS INDICATE LOAD BEARING POINTS OR WALLS THAT STACK. ADDITIONAL LOAD BEARING POINTS MAY BE REQUIRED AND MUST BE CALCULATED WHEN FLOOR SYSTEM IS ENGINEERED.
- 7.0 ALL EXTERIOR OPENINGS TO BE LOAD BEARING.
- 8.0 WHEN ENGINEERED TRUSSES TO BE USED TRUSS DESIGN & SPACING TO BE PER ENGINEER'S SPECIFICATIONS.
- 9.0 ALL WALLS OVER 10'-0" IN HEIGHT TO BE FRAMED WITH 2X6 STUDS. IF WALLS OVER 10'-0" IN HEIGHT ARE NOT BUILT WITH 2X6 STUDS THEY MUST BE BUILT WITH DOUBLE 2X4 STUDS AT 12" O.C.
- 10.0 BUILDER ACCEPTS FULL RESPONSIBILITY FOR CHECKING PLANS TO ASSURE CONFORMITY TO CURRENT LOCAL BUILDING CODES. SHOULD ANY CHANGES BE MADE TO THESE PLANS BY BUILDER OR HIS REPRESENTATIVES WITHOUT CONTACTING THE DESIGNER, THE BUILDER WILL ACCEPT FULL LIABILITY FOR AMENDED PLANS.
- 11.0 ALL LOAD BEARING HEADERS & CONCEALED OR DROPPED BEAMS TO BE DESIGNED PER ENGINEER OR BUILDER.


**ROOF OUTLINE**

SCALE 1/4" = 1'-0"




**FRONT ELEVATION**

SCALE 1/4" = 1'-0"




**REAR ELEVATION**

SCALE 1/4" = 1'-0"




**RIGHT ELEVATION**

SCALE 1/4" = 1'-0"



**LEFT ELEVATION**

SCALE 1/4" = 1'-0"



**FLOOR PLAN**

SCALE 1/4" = 1'-0"


SQUARE FOOTAGE CALCS.	
HEATED	649 s.f.

Casa Uber Alles 7.0

Fredericksburg High School  
Fredericksburg, TX 78624

design visions

unique residential design  
830. 992. 3640 www.designvisions.tx.com



Copyright © 2021 All Rights Reserved. These designs/drawings are the sole property of design visions of austin and may not be reproduced in any form, by any method, for any purpose without previous written permission.


PROJECT:  
Casa Uber Alles  
7.0

A-1  
1 of 2

date: 8.19.22  
project #: 22070

GENERAL INT. ELEV. NOTES

- 1.0 WIDTH DIMENSIONS ARE APPROXIMATE. MEASURE ON SITE FOR EXACT WIDTH OF CABINET AREAS.
- 2.0 STANDARD STILES BETWEEN DOORS & DRAWERS ARE SHOWN. CHECK WITH CONTRACTOR FOR EXACT STILE PLACEMENT & WIDTH.
- 3.0 VERIFY CABINETS AND CABINET STYLE(S) WITH OWNER. INTERIOR DESIGNER OR BUILDER. STANDARD DOORS & DRAWERS ARE SHOWN. CHECK WITH CONTRACTOR FOR EXACT DOOR & DRAWER PLACEMENT, FRONTS & HARDWARE.
- 4.0 SHELVES ARE SPACED EQUALLY UNLESS NOTED. ADJUSTABLE SHELVES IN ALL CABINET LOCATIONS, EXCEPT WHERE NOTED AS fixed OR GIVEN A SPECIFIC HEIGHT.
- 5.0 LAVATORIES AND SINKS SHOWN ARE NOT ACTUAL FIXTURE. CHECK WITH BUILDER/DESIGNER/OWNER FOR ACTUAL FIXTURE STYLE AND SIZE.
- 6.0 APPLIANCE DIMENSIONS MAY VARY. CHECK WITH BUILDER FOR EXACT DIMENSIONS.
- 7.0 PROVIDE VENT HOLES AS REQUIRED FOR AIR CIRCULATION OF IN-CABINET COMPUTER EQUIPMENT.
- 8.0 PROVIDE 2" GROMMET AT ALL KNEE SPACES OF DESKS FOR CORD & CABLE ACCESS TO PLUGS BELOW.
- 9.0 PROVIDE GROMMETS AS REQ'D. FOR CABLES AT ENTERTAINMENT CENTERS, MEDIA CENTERS &/OR AUDIO/VIDEO CENTERS.
- 10.0 CABINET CONTRACTOR TO PROVIDE AND INSTALL END PANELS TO MATCH CABINET FACE DESIGNS. PROVIDE AT ALL END PANEL LOCATIONS AND AT ALL WALL FRONTS AT fixed BAR LOCATIONS. PROVIDE MATCHING OR PER DESIGNER SELECTION BULKHEADS AS REQUIRED FOR STURDY TOP SUPPORT.
- 11.0 TOP & SPLASH MATERIAL AT ALL CABINETS TO BE AS PER SPECS.
- 12.0 CROWN MOLDING, INTERIOR WINDOW/DOOR TRIM, BASEBOARD & TILE SHOWN TO BE PER OWNER &/OR INTERIOR DESIGNER.
- 13.0 SPECIALTY CABINETS, HARDWARE, AND/OR ACCESSORIES TO BE COORDINATED BETWEEN DESIGNER, OWNER & SUBCONTRACTOR AS REQUIRED.



INTERIOR ELEVATIONS

SCALE 3/8" = 1'-0"

GENERAL ELECTRICAL NOTES:

- 1.0 ALL WORK DONE UNDER THIS SECTION SHALL CONFORM WITH THE CURRENT NATIONAL ELECTRICAL CODE AND LOCAL CODE REGULATIONS. THE CONTRACTOR SHALL PERFORM ALL WORK IN CONFORMITY WITH THESE REGULATIONS WHETHER OR NOT SUCH WORK IS SPECIFICALLY SHOWN ON DRAWINGS.
- 2.0 ELECTRICAL SUBCONTRACTOR TO MAKE ALL NECESSARY ELEC. CONNECTIONS AND BE RESPONSIBLE FOR ALL ELECTRICAL SERVICE AT MECHANICAL ROOM. ELECTRICAL CONTRACTOR TO COORDINATE AS REQUIRED WITH MECHANICAL SUBCONTRACTOR.
- 3.0 THE ELECTRICAL CONTRACTOR SHALL COORDINATE HIS WORK WITH THE WORK OF OTHER TRADES AND HAVE HIS WORK SCHEDULED SO AS NOT TO DELAY THE WORK OF OTHERS.
- 4.0 THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSPECTION AND APPROVAL OF WIRING, INSTALLATION OF FIXTURES AND EQUIPMENT, AND FOR FINAL ACCEPTANCE OF THE COMPLETE ELECTRICAL INSTALLATIONS BY THE UNDERWRITERS AND BY LOCAL ELECTRICAL INSPECTORS.
- 5.0 COORDINATE WITH CONSTRUCTION SPECIFICATIONS FOR ANY APPLICABLE ALLOWANCES FOR ELECTRICAL.
- 6.0 ALL RECESSED DOWNLIGHTS TO BE THERMAL RATED AND INCLUDED IN BASE BID WITH TRIM RINGS AS SPECIFIED BY INTERIOR DESIGNER/OWNER TO MATCH ADJACENT FINISH. PROVIDE SAMPLE OF FINISH FOR APPROVAL PRIOR TO PURCHASE.
- 7.0 ALL SWITCHES TO BE @ 3'-0" A.F.F. TO CENTER LINE OF SWITCH PLATE UNLESS NOTED OTHERWISE.
- 8.0 PREWIRE FOR SECURITY SYSTEM PER OWNERS REQUEST.
- 9.0 GANG ALL SWITCHES AND OUTLETS WHERE POSSIBLE.
- 10.0 VERIFY LOCATION OF & TYPE OF POWER TO ALL APPLIANCES.
- 11.0 OUTLETS WITHIN 36" OF A SINK OR LAVATORY TO BE ON A G-F.I. CIRCUIT. ADDITIONAL GFI AS REQUIRED BY CODE.
- 12.0 NO SWITCHES TO BE WITHIN 5'-0" OF A TUB OR SHOWER.
- 13.0 HEIGHT OF OUTLETS FROM FLOOR TO CENTER LINE OF OUTLET TO BE 12" TYPICAL UNLESS NOTED OTHERWISE.
- 14.0 LOCATION OF ALL FLOOR OUTLETS & FLOOR PHONE OUTLETS TO BE VERIFIED BY OWNER.
- 15.0 PROVIDE PHONE & CATV OUTLETS PER PLAN OR PER OWNERS REQUEST.
- 16.0 NOTE TO SUBCONTRACTOR: CENTER LIGHT OVER PEDESTAL LAV. WHERE SHOWN.
- 17.0 SUPPLY 220v & 110v OR GAS & 110v TO HVAC UNIT(S) IN ATTIC. (REFER TO SPECS) PROVIDE POWER AS REQ'D. AT A/C COMPRESSOR UNITS.
- 18.0 PROVIDE FOR LIGHT NEAR HVAC UNIT(S) IN ATTIC.
- 19.0 PROVIDE 2" GROMMET AT ALL KNEE SPACES OF DESKS FOR CORD & CABLE ACCESS TO PLUGS BELOW. PROVIDE GROMMETS AS REQ'D. FOR CABLES & ENTERTAINMENT CENTERS, MEDIA CENTERS &/OR AUDIO/VIDEO CENTERS.
- 20.0 MEDIA COMBINATION OUTLET(S) TO PROVIDE CONNECTIONS FOR ELECTRICAL & VARIOUS MEDIA/TELECOMMUNICATIONS SYSTEMS.
- 21.0 PROVIDE BLOCKING FOR CEILING FANS WHERE SPECIFIED.
- 22.0 PROVIDE FOR MOTION SENSORS AT ALL GARAGE DOORS WITH OPENERS.
- 23.0 PROVIDE ELECTRIC FOR POOL &/OR SPA EQUIP. & LIGHTS. PROVIDE ELECTRIC AND SWITCHING FOR LANDSCAPE LIGHTING: FOUNTAINS, ETC. VERIFY LOCATION WITH BUILDER OR OWNER.
- 24.0 SMOKE DETECTORS SHOULD BE LOCATED IN EACH BEDROOM AND AS SHOWN. ALL SMOKE DETECTORS SHALL BE HARD WIRED TO PRIMARY ELECTRICAL SERVICES WITH BATTERY BACKUP.
- 25.0 ARC-FAULT PROTECTION REQUIRED IN ALL HABITABLE AREAS (WITH THE EXCEPTION OF BATHROOMS, KITCHEN, & LAUNDRY).
- 26.0 ALL RECEPTACLE OUTLETS MUST BE LISTED TAMPER RESISTANT.

ELECTRICAL LEGEND

SWITCH	CEILING MOUNTED FIXTURE
SWITCH - 3 WAY	RECESSED CAN LIGHT
SWITCH - 4 WAY	RECESSED CAN LIGHT WATERPROOF
SWITCH - DIMMER	EYEBALL SPOTLIGHT
SWITCH - GFI	WALL MOUNT FIXTURE
ALL WET AREA SWITCHES TO BE GFI	FLOOR LIGHT (TYPE PER SPECS.)
SWITCH - WATERPROOF	TRACK LIGHT
PHONE OUTLET - FAX	FLOOD LIGHT (SHIELDED)
PHONE OUTLET	VENT/LIGHT COMBO
FLR. PHONE OUTLET	VENT/LIGHT/HEAT COMBO
FLOOR OUTLET	HEAT LITE
TELEVISION OUTLET	VENT/EXHAUST
PUSHBUTTON FOR GAR. DR. OPENER	LOW VOLT. HALOGEN
JUNCTION BOX	GAS VALVE
OUTLET - 110V DUPLEX	GAS KEY
OUTLET - 110V QUADPLEX	RESER LITE (RCSCD)
OUTLET - 110V WATERPROOF	COMBINATION MEDIA OUTLET
OUTLET - 220V	CATV S CONNECTION
SPLIT WIRE FOR SWITCH PLUG SWITCH TOP PLUG ONLY	ELEC. PANEL
EXT. DOOR BELL	LOW-VOLT. DIRECTIONAL SPOT
CHIMNEY	LOW-VOLT. PIN-LITE SPOT
THERMOSTAT	MINI-FLOOD LIGHT
SMOKE DETECTOR	
INTERCOM/SPEAKER	
CARBON MONOXIDE DETECTOR	
HEAT DETECTOR	
LOW-VOLT. UPLITE	
LOW-VOLT. PENDANT SPOT	
WALLWASH FIXTURE	
SPEAKER	
SMOKE/CARBON MONOXIDE DETECTOR	
CLG. FAN W/ LIGHT KIT	CEILING FAN (WITHOUT LIGHT KIT)

design visions  
unique residential design

Copyright © 2021 All Rights Reserved. These designs/drawings are the sole property of design visions of Austin and may not be reproduced in any form, by any method, for any purpose without previous written permission.

PROJECT:  
Casa Uber Alles  
7.0

A-2  
2 of 2

date: 8.19.22  
project #: 22070